

# SEYPOS®

Touch Scan Print

## Monitor Táctil TM 515



Diseñado, desarrollado y construido para ofrecer las soluciones táctiles más rentables para una venta rápida en supermercados, bares, restaurantes, cafeterías....

Fiable, duradero y resistente a las salpicaduras de líquido con la firmeza justa de pantalla en el toque

# Monitor táctil

## Especificaciones técnicas TM 515

<b>Model</b>	TM-515
<b>Diagonal Size</b>	15" 4:3
<b>Touch Technology</b>	5-wires Resistive Touch Panel, Life: 10 Million Touches
<b>Touch Interface</b>	Dual USB & RS232 Interface or Single USB Interface Option
<b>OS Support</b>	DOS, Windows 2000/XP/Vista/7 32&64-bit, Linux, iMac etc.
<b>Useful Screen Area</b>	304 mm (H) x 228 mm (V)
<b>Monitor Dimensions (without stand)</b>	360(L)×53(W)×303(H)(mm)
<b>Native (optimal) Resolution</b>	1024 X 768 @ 60 Hz
<b>Colors</b>	16.7 Million
<b>Brightness(typical)</b>	LCD Panel: 250 nits
<b>Response Time - total (typical)</b>	8 msec
<b>Viewing Angle (typical)</b>	Horizontal: ±80° or 160° Total
<b>Contrast Ratio (typical)</b>	600:1
<b>On-screen Display (OSD)</b>	Controls (front): Auto, -, +, Menu, Power Settings: Contrast, Brightness, H/V Position, RGB (color Temp), Clock, Phase, Recall Languages: English, German, Spanish, Japanese, French, Russian, Chinese
<b>Input Video Signal Connector</b>	D-sub 15-pin VGA Type
<b>Audio</b>	2 X Built-in Speakers (*option)
<b>Power Supply</b>	External Power Adaptor 50W; AC: 100~240V, 50/60Hz; DC: +12VDC, 4.16A
<b>Power Consumption (typical)</b>	<30 W
<b>Mounting Applicaion</b>	75 mm VESA Mount
<b>Weight</b>	N.W.:4.51Kg / G.W.:6.42Kg
<b>Shipping Box Dimensions</b>	440(L)×185(W)×425(H)(mm)
<b>Other Features</b>	Security Lock Receptacle
<b>Temperature</b>	Operating: 0°C To 40°C (32°F To 104°F), Storage: -20°C To 60°C (-4°F To 140°F)
<b>Humidity(noncondensing)</b>	Operating: 20%-80%, Storage: 10%-90%
<b>Certificates</b>	CE, FCC, RoHS
<b>Options</b>	Wall Mount Or Ceiling Mount Brackets



Adjustable



Stand



Interface

**SEYPOS**®

Touch Scan Print